



Specification

Model No.:	RS-FT108W316X-A(88157) / RS-FT144W316X-A(88157)
Front cover & Housing:	Stainless steel 316L
Dimensions:	D315*H46mm (Nozzle hole size: 80mm)
Tempered Glass:	10mm thickness
LED chip:	CREE / Edison / Epistar
LED Q'ty:	36pcs 3W LED / 36pcs 3in1 LED / 36pcs 4in1 LED
Cable gland:	Stainless steel 316L PG13.5
Driver:	Constant current driver
Lens:	Clear, Bead, Frosted
Beam Angle Options:	10° 30° 45° 60° 90°
Power Cable:	AWG 5/18 or AWG 3/18 SOW rubber cable
Protection Class:	IP68
Environment:	Dry / Submerged
Mounting Hardware:	Floor Recessed / Nozzle fixed
Net Weight:	8.8kgs with 1.5m cable
Lifetime:	>50000H

Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88157.363.01	2700-3000K	36*3	V+/V-	DC24	4500	108	5040
88157.363.02	4000-4500K	36*3	V+/V-	DC24	4500	108	5220
88157.363.03	5000-5500K	36*3	V+/V-	DC24	4500	108	5580
88157.363.04	6000-6500K	36*3	V+/V-	DC24	4500	108	5580
88157.363.05	Red	36*3	V+/V-	DC24	3000	72	1260
88157.363.06	Green	36*3	V+/V-	DC24	4500	108	3240
88157.363.07	Blue	36*3	V+/V-	DC24	4500	108	1440
88157.363.08	Yellow	36*3	V+/V-	DC24	4500	108	3420
88157.363.09	RGB-DMX512 (3 channel)	36*3	V+/V- /D+/D-/GND	DC24	R: 1000 B: 1500 G: 1500	R: 24 B: 36 G: 36	R: 420 B: 480 G: 1080
88157.363.12	RGBV+ (build-in CC driver)	36*3	R/G/B/V+	DC24	R: 1000 B: 1500 G: 1500	R: 24 B: 36 G: 36	R: 420 B: 480 G: 1080
88157.363.13	RGB-DMX512 (3 channel)	36*3in1	V+/V- /D+/D-/GND	DC24	R: 1500 B: 1500 G: 1500	R: 36 B: 36 G: 36	R: 900 B: 1080 G: 2160
88157.364.14	RGBW-DMX512 (4 channel)	36*4in1	V+/V- /D+/D-/GND	DC24	R: 1500 B: 1500 G: 1500 W: 1500	R: 36 B: 36 G: 36 W: 36	R: 900 B: 1080 G: 2160 W: 3240

