




Product Size



Specification

Model No.:	RS-PAR56-15W(88127)
Front cover & Housing:	ABS+PC
Dimensions:	D290*H62mm
Tempered Glass:	PC cover
LED chip:	SMD 5050 Epistar
LED Q'ty:	75pcs *0.2W
Cable gland:	/
Driver:	Constant current driver
Lens:	120° bead PC cover
Beam Angle Options:	120°
Power Cable:	2*1.0mm ² PVC cable / 4*0.75mm ² / 2*1.0mm ² +3*0.75mm ² VDE rubber cable
Protection Class:	IP68
Environment:	Pool
Mounting Hardware:	Pool wall mounting
Net Weight:	1.2kgs with 1.5m cable
Lifetime:	>50000H

Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88127.075.01	2700-3000K	75*0.2	V+/V-	DC12	1250	15	1200
88127.075.02	4000-4500K	75*0.2	V+/V-	DC12	1250	15	1275
88127.075.03	5000-5500K	75*0.2	V+/V-	DC12	1250	15	1350
88127.075.04	6000-6500K	75*0.2	V+/V-	DC12	1250	15	1425
88127.075.05	Red	75*0.2	V+/V-	DC12	1250	15	300
88127.075.06	Green	75*0.2	V+/V-	DC12	1250	15	600
88127.075.07	Blue	75*0.2	V+/V-	DC12	1250	15	375
88127.075.08	Yellow	75*0.2	V+/V-	DC12	1250	15	1050
88127.075.09	RGB-DMX512 (3 channel)	75*0.2	V+/V-/D+/D-/GND	DC12	R: 416 B: 416 G: 416	R: 5 B: 5 G: 5	R: 100 B: 125 G: 200
88127.075.10	Auto changing color	75*0.2	V+/V-	AC12	R: 416 B: 416 G: 416	R: 5 B: 5 G: 5	R: 100 B: 125 G: 200
88127.075.11	RF remote control	75*0.2	V+/V-	DC12	R: 416 B: 416 G: 416	R: 5 B: 5 G: 5	R: 100 B: 125 G: 200
88127.075.12	RGBV+ (build-in CC driver)	75*0.2	R/G/B/V+	DC12	R: 416 B: 416 G: 416	R: 5 B: 5 G: 5	R: 100 B: 125 G: 200

