




Product Size



Specification

Model No.:	RS-UG1W(88231)
Front cover & Housing:	Aluminum body
Dimensions:	D28*H57mm
Tempered Glass:	2.5mm thickness
LED chip:	Cree
LED Q'ty:	1pc 1W LED
Cable gland:	Nickel plated brass PG7
Driver:	Constant current driver
Lens:	No lens
Beam Angle Options:	120°
Power Cable:	2*1.0mm ² VDE rubber cable
Protection Class:	IP65
Environment:	Dry
Mounting Hardware:	Embedded System
Net Weight:	0.15kgs with 1m cable
Lifetime:	>50000H

Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88231.011.01	2700-3000K	1*1	V+/V-	DC12-24	83 / 41	1	90
88231.011.02	4000-4500K	1*1	V+/V-	DC12-24	83 / 41	1	95
88231.011.03	5000-5500K	1*1	V+/V-	DC12-24	83 / 41	1	100
88231.011.04	6000-6500K	1*1	V+/V-	DC12-24	83 / 41	1	100
88231.011.05	Red	1*1	V+/V-	DC12-24	83 / 41	1	25
88231.011.06	Green	1*1	V+/V-	DC12-24	83 / 41	1	60
88231.011.07	Blue	1*1	V+/V-	DC12-24	83 / 41	1	30
88231.011.08	Yellow	1*1	V+/V-	DC12-24	83 / 41	1	70

