



## Specification

<b>Model No.:</b>	RS-UG1W316X-N(88256)
<b>Front cover &amp; Housing:</b>	Stainless steel 316
<b>Dimensions:</b>	D62*H94mm
<b>Tempered Glass:</b>	PC cover inside
<b>LED chip:</b>	Cree
<b>LED Q'ty:</b>	1pc 1W LED
<b>Cable gland:</b>	Nickel plated brass PG7
<b>Driver:</b>	Constant current driver
<b>Lens:</b>	/
<b>Beam Angle Options:</b>	90°
<b>Power Cable:</b>	2*1.0mm <sup>2</sup> / 3*0.75mm <sup>2</sup> VDE rubber cable
<b>Protection Class:</b>	IP67
<b>Environment:</b>	Dry
<b>Mounting Hardware:</b>	Embedded System
<b>Net Weight:</b>	0.6kgs with 1m cable
<b>Lifetime:</b>	>50000H

## Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88256.011.01	2700-3000K	1*1	V+/V- or L/N/G	AC/DC12, AC90-230	83 / 4.5-9	1	90
88256.011.02	4000-4500K	1*1	V+/V- or L/N/G	AC/DC12, AC90-230	83 / 4.5-9	1	95
88256.011.03	5000-5500K	1*1	V+/V- or L/N/G	AC/DC12, AC90-230	83 / 4.5-9	1	100
88256.011.04	6000-6500K	1*1	V+/V- or L/N/G	AC/DC12, AC90-230	83 / 4.5-9	1	100
88256.011.05	Red	1*1	V+/V- or L/N/G	AC/DC12, AC90-230	83 / 4.5-9	1	25
88256.011.06	Green	1*1	V+/V- or L/N/G	AC/DC12, AC90-230	83 / 4.5-9	1	60
88256.011.07	Blue	1*1	V+/V- or L/N/G	AC/DC12, AC90-230	83 / 4.5-9	1	30
88256.011.08	Yellow	1*1	V+/V- or L/N/G	AC/DC12, AC90-230	83 / 4.5-9	1	70

