




### Product Size



### Specification

<b>Model No.:</b>	RS-FT36W316X-A(88133)
<b>Front cover &amp; Housing:</b>	Stainless steel 316L
<b>Dimensions:</b>	D250*H59mm (Nozzle hole size: 47mm)
<b>Tempered Glass:</b>	10mm thickness
<b>LED chip:</b>	CREE
<b>LED Q'ty:</b>	12pcs 3W LED / 12pcs 4in1 LED
<b>Cable gland:</b>	Stainless steel 316L PG13.5
<b>Driver:</b>	Constant current driver
<b>Lens:</b>	Clear, Bead, Frosted
<b>Beam Angle Options:</b>	10° 20° 30° 45° 60° 90°
<b>Power Cable:</b>	AWG 5/18 or AWG 3/18 SOW rubber cable
<b>Protection Class:</b>	IP68
<b>Environment:</b>	Dry / Submerged
<b>Mounting Hardware:</b>	Floor Recessed / Nozzle fixed
<b>Net Weight:</b>	5.0kgs with 1.5m cable
<b>Lifetime:</b>	>50000H

### Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88133.123.01	2700-3000K	12*3	V+/V-	AC/DC12-24	3000 / 1500	36	1680
88133.123.02	4000-4500K	12*3	V+/V-	AC/DC12-24	3000 / 1500	36	1776
88133.123.03	5000-5500K	12*3	V+/V-	AC/DC12-24	3000 / 1500	36	1860
88133.123.04	6000-6500K	12*3	V+/V-	AC/DC12-24	3000 / 1500	36	1860
88133.123.05	Red	12*3	V+/V-	AC/DC12-24	2000 / 1000	24	420
88133.123.06	Green	12*3	V+/V-	AC/DC12-24	3000 / 1500	36	1080
88133.123.07	Blue	12*3	V+/V-	AC/DC12-24	3000 / 1500	36	480
88133.123.08	Yellow	12*3	V+/V-	AC/DC12-24	3000 / 1500	36	1140
88133.123.09	RGB-DMX512 (3 channel)	12*3	V+/V- /D+/D-/GND	DC24	R: 333 B: 500 G: 500	R: 8 B: 12 G: 12	R: 140 B: 160 G: 360
88133.123.10	Auto changing color	12*3	V+/V-	AC24	R: 333 B: 500 G: 500	R: 8 B: 12 G: 12	R: 140 B: 160 G: 360
88133.123.12	RGBV+ (build-in CC driver)	12*3	R/G/B/V+	DC24	R: 333 B: 500 G: 500	R: 8 B: 12 G: 12	R: 140 B: 160 G: 360
88133.124.13	RGBW-DMX512 (4 channel)	12*4in1	V+/V- /D+/D-/GND	DC24	R: 500 B: 500 G: 500 W: 500	R: 12 B: 12 G: 12 W: 12	R: 300 B: 360 G: 720 W: 1080

