




Product Size



Specification

Model No.:	RS-FT36W316X-B(88135) / RS-FT60W316X-B(88135)
Front cover & Housing:	Stainless steel 316L
Dimensions:	D184*H59mm (Nozzle hole size: 47mm)
Tempered Glass:	10mm thickness
LED chip:	CREE / EDISON
LED Q'ty:	12pcs 3W LED / 12pcs 3in1 LED / 12pcs 4in1 LED / 48pcs 3W LED
Cable gland:	Stainless steel 316L PG13.5
Driver:	Constant current driver
Lens:	Clear, Bead, Frosted
Beam Angle Options:	10° 20° 30° 45° 60° 90°
Power Cable:	AWG 5/18 or AWG 3/18 SOW rubber cable
Protection Class:	IP68
Environment:	Dry / Submerged
Mounting Hardware:	Surface Mounted System / Nozzle fixed
Net Weight:	4.5kgs with 1.5m cable
Lifetime:	>50000H

Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88135.123.01	2700-3000K	12*3	V+/V-	AC/DC24	1500	36	1680
88135.123.02	4000-4500K	12*3	V+/V-	AC/DC24	1500	36	1776
88135.123.03	5000-5500K	12*3	V+/V-	AC/DC24	1500	36	1860
88135.123.04	6000-6500K	12*3	V+/V-	AC/DC24	1500	36	1860
88135.123.05	Red	12*3	V+/V-	AC/DC24	1000	24	420
88135.123.06	Green	12*3	V+/V-	AC/DC24	1500	36	1080
88135.123.07	Blue	12*3	V+/V-	AC/DC24	1500	36	480
88135.123.08	Yellow	12*3	V+/V-	AC/DC24	1500	36	1140
88135.123.09	RGB-DMX512 (3 channel)	12*3	V+/V-/D+/D-/GND	AC/DC24	R: 333 B: 500 G: 500	R: 8 B: 12 G: 12	R: 140 B: 160 G: 360
88135.123.10	Auto changing color	12*3	V+/V-	AC24	R: 333 B: 500 G: 500	R: 8 B: 12 G: 12	R: 140 B: 160 G: 360
88135.123.12	RGBV+ (build-in CC driver)	12*3	R/G/B/V+	DC24	R: 333 B: 500 G: 500	R: 8 B: 12 G: 12	R: 140 B: 160 G: 360
88135.123.13	RGB-DMX512 (3 channel)	12*3in1	V+/V-/D+/D-/GND	AC/DC24	R: 500 B: 500 G: 500	R: 12 B: 12 G: 12	R: 300 B: 360 G: 720
88135.124.14	RGBW-DMX512 (4 channel)	12*4in1	V+/V-/D+/D-/GND	AC/DC24	R: 500 B: 500 G: 500 W: 500	R: 12 B: 12 G: 12 W: 12	R: 300 B: 360 G: 720 W: 1080
88135.483.15	RGBW-DMX512 (4 channel)	48*3	V+/V-/D+/D-/GND	AC/DC24	R: 625 B: 625 G: 625 W: 625	R: 15 B: 15 G: 15 W: 15	R: 525 B: 600 G: 1350 W: 1425

