



Specification

Model No.:	RS-UG9W-PM(88230)
Front cover & Housing:	304 Stainless steel+Aluminum body+Plastic installation box
Dimensions:	D160*H90mm
Tempered Glass:	8mm thickness
LED chip:	Cree / Epistar
LED Q'ty:	9pcs 1W LED
Cable gland:	Nickel plated brass PG9
Driver:	Constant current driver
Lens:	Clear, Bead, Frosted
Beam Angle Options:	10° 30° 45° 60° 90°
Power Cable:	2*1.0mm ² / 3*0.75mm ² / 4*0.75mm ² / 2*1.0mm ² +3*0.75mm ² VDE rubber cable
Protection Class:	IP67
Environment:	Dry
Mounting Hardware:	Embedded System
Net Weight:	1.4kgs with 1m cable
Lifetime:	>50000H

Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88230.091.01	2700-3000K	9*1	V+/- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	810
88230.091.02	4000-4500K	9*1	V+/- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	855
88230.091.03	5000-5500K	9*1	V+/- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	900
88230.091.04	6000-6500K	9*1	V+/- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	900
88230.091.05	Red	9*1	V+/- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	225
88230.091.06	Green	9*1	V+/- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	540
88230.091.07	Blue	9*1	V+/- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	270
88230.091.08	Yellow	9*1	V+/- or L/N/G	AC/DC12-24, AC90-230	750 / 375 / 40-48	9	630
88230.091.09	RGB-DMX512 (3 channel)	9*1	V+/- /D+/D-/GND	AC/DC12-24	R: 250 / 125 B: 250 / 125	G: 250 / 125	R: 75 B: 90
88230.091.10	Auto changing color	9*1	V+/-	AC12-24	R: 250 / 125 B: 250 / 125	G: 250 / 125	R: 75 B: 90
88230.091.12	RGBV+ (build-in CC driver)	9*1	R/G/B/V+	DC12-24	R: 250 / 125 B: 250 / 125	G: 250 / 125	R: 75 B: 90

